

T1230A

Thermoplastic Polymers

Airtop || Rubber Air Hose

Compressed Air Applications



Description

A 15 bar, flexible rubber hose for compressed air. Phthalate free.

Applications

Ideal for use on compressor equipment used to supply pneumatic tools for worksite use in industries such as construction and civil engineering.

Construction

Liner

Smooth, black NBR/SBR.

Reinforcement/s

High strength polyester braid.

Cover

Smooth, black, SBR.

Temperature Range

-40°C to +80°C

Specification								
Size	ID (mm)	OD (mm)	Wall (mm)	Bend Radius (mm)	WP (bar)	BP (bar)	Weight (g/m)	Product Code
3/8"	10	17	3.5	100	15	45	220	T1230A-010
-	13	20	3.5	120	15	45	260	T1230A-013
5/8"	16	23	3.5	160	15	45	310	T1230A-016
3/4"	20	29	4.5	200	15	45	510	T1230A-020
1"	25	34	4.5	250	15	45	600	T1230A-025

Advantages

Due to its optimal design, Airtop is a hose which offers a very attractive cost/benefit ratio. Suited for all-weather use, it is the ideal hose for supplying compressed air on worksites.

Connectors

Quick fittings with claw clamps of Ø 1.1 in.