


T5715L

Rubber Hose

Dairyflex® Lite Easy Operation Food & Dairy Suction & Delivery Hose

Food & Beverage Applications



Description

A 10 bar, very flexible, light handling, food quality, suction and delivery hose for fatty foods and dairy produce.

Construction

Liner

Smooth, white, NBR rubber compound. This food quality liner is odourless and taste free.

Reinforcement/s

High strength synthetic plies with steel wire spirals.

Cover

Smooth, blue, cloth impression NBR rubber which is resistant to ozone, abrasion and weathering.

Standards & Specifications

FDA 21.CFR.177.2600, BfR D.M.21/03/73, ADI Free, CE 1935/2004

Temperature Range

-30°C to +100°C (Max 20 mins +130°C for sterilisation)

Specification									
Size	ID (mm)	OD (mm)	Wall (mm)	Bend Radius (mm)	WP (bar)	BP (bar)	Vacuum (bar)	Weight (g/m)	Product Code
1 1/4"	32	44	6.0	80	10	30	0.9	1100	T5715L-032
1 1/2"	38	50	6.0	125	10	30	0.9	1230	T5715L-038
2"	51	64	6.5	150	10	30	0.9	1900	T5715L-051
2 1/2"	63.5	76.5	6.5	160	10	30	0.9	2300	T5715L-063
3"	76	90	7.0	190	10	30	0.9	2900	T5715L-076
4"	102	118	8.0	200	10	30	0.9	3800	T5715L-102