



Description

A 10 bar, lightweight, crush resistant, food quality, suction and delivery hose for fatty foods and dairy produce.

Construction

Liner

Smooth, white, NR rubber compound. This food quality liner is odourless and taste free.

Reinforcement/s

High strength synthetic plies with nylon spirals.

Cover

Smooth, blue, cloth impression NR rubber which is resistant to ozone, abrasion and weathering.

Standards & Specifications

FDA 21.CFR.177.2600, BfR D.M.21/03/73, ADI Free, CE 1935/2004

Temperature Range

-30°C to +100°C (Max 20 mins +130°C for sterilisation)

Specification									
Size	ID (mm)	OD (mm)	Wall (mm)	Bend Radius (mm)	WP (bar)	BP (bar)	Vacuum (bar)	Weight (g/m)	Product Code
1 1/4"	32	44	6.0	96	10	30	0.4	1040	T5718C-032
1 1/2"	38	50	6.0	150	10	30	0.4	1140	T5718C-038
2"	51	64	6.5	180	10	30	0.4	1540	T5718C-051
2 1/2"	63.5	76	6.2	192	10	30	0.4	2400	T5718C-063
3"	76	90	7.0	228	10	30	0.4	2800	T5718C-076
4"	102	118	8.0	240	10	30	0.4	4000	T5718C-102